



Intermec

Product Profile

- For use in industrial locations where flammable gases, combustible dusts or ignitable fibers may be present.
- Powerful Intel® XScale™ processor
- Microsoft® Windows® Mobile software for Pocket PC
- Built-in wireless LAN and Bluetooth™ connectivity for communication without wires
- Advanced linear imaging technology to read barcodes quickly and reliably
- Bright color display provides easy readability under all lighting conditions
- Ergonomically designed for comfortable full-day use
- Part of a comprehensive solution including printers, application software, communications infrastructure products, peripherals, and accessories



Cisco
Compatible

730 COLOR I-SAFE MOBILE COMPUTER

Intermec's 730 Intrinsically Safe (I-Safe) certified device provides for the ability to extend the 700 Color Series mobile application benefits into hazardous industrial locations where flammable gases, combustible dusts or ignitable fibers may be present.

Building on the standards set by the highly configurable 700 Color Series, the 730 model provides a defined feature set which includes a sharp color display, local area and personal area (Bluetooth) wireless radios, as well as a linear imager that delivers high-speed barcode reading performance.

The introduction of hazardous environment certifications within the successful 700 Series product offering

allows for cross-departmental standardization for both hazardous and non-hazardous environments, minimizing your enterprise's total cost of ownership.

Meeting the stringent Underwriters Laboratory (UL) certification requirements for Division 1, Class I, Class II or Class III; the 730 device is tough enough to handle the daily rigors of your frontline business.

Whether your application is standalone, client-server, browser-based, or terminal emulation, the 730 is the right tool.



Intermec

Physical Characteristics

Length: 178 mm (7.0 in.)
Width: 89 mm (3.5 in.)
Height: 38 mm (1.5 in.)
Weight: 493 grams (17.6 oz)

Environmental**Operating Temp:**

-10 to 40°C (+14° to +104°F)

Storage Temp:

-20° to +60°C (-4° to +140°F)

Relative Humidity:

5% to 95% (non-condensing)

Rain and Dust Resistance:

IP54 compliant

Drop Spec: Underwriters Laboratory (UL)

1m (3.3') drop specifications

Power

Battery Type: Lithium-Ion, 3.6V, (1 x 2400 mAh cell), customer replaceable

Battery Capacity: 8.64 Watt-hours

Recharging Time: 4 hours with multi-pack battery charger

Microprocessor

Intel® XScale™ PXA255 Applications Processor, 400 MHz

Operating System

Microsoft® Windows® Mobile software for Pocket PC

Memory and Storage

RAM Memory: 64 MB

Flash ROM: 64 MB; includes ROM folder for application storage

Expansion Slot

128 MB Secure Digital (SD) customer accessible outside of hazardous environment

Display

Transflective TFT all-light readable color display with LED backlight, 240x320 pixels, 89 mm (3.5 in) diagonal, 64 K colors

Standard Communications

RS232, USB, IrDA 1.1 (115 kbps)

Integrated Wireless

802.11b WLAN (Wi-Fi® certified) Bluetooth™ compatible module

Integrated Scanner Options

Linear imager

Cisco Compatible Extensions

Version 1 Supported

LEAP

CKIP

VLAN

Regulatory Approvals

FCC Part 15 Class B

UL Listing

Hazardous Certification

Underwriters Laboratories, Inc. approval for U.S. and Canada

Class I, Division 1, Groups C, D

Class II, Division 1, Groups F, G

Class III, Division 1

Temperature Code T4 (≤ 135° C)

Imager Specifications

Density	Minimum	Maximum
4 mil (0.1mm)	3.7 in. (95 mm)	5.4 in. (136 mm)
12 mil (0.3mm)	1.8 in. (45 mm)	9.4 in. (240 mm)
20 mil (0.5mm)	1.7 in. (44 mm)	11.8 in. (300 mm)
39 mil (1mm)	4.7 in. (120 mm)	15.7 in. (400 mm)
100% UPC	1.8 in. (45 mm)	9.4 in. (240 mm)
25% UPC	2.4 in. (61 mm)	6.2 in. (157 mm)

Key Accessories

For use in hazardous environments

128 MB SD Storage Cards

Scanning Handles

For use in non-hazardous environments

Desktop connectivity docks

Battery Pack chargers

Printers

* Bluetooth is a trademark owned by Bluetooth SIG, Inc., USA.

Microsoft, Windows, the Windows logo, Windows Media, Outlook, and ActiveSync are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Intel and XScale are trademarks of Intel Corporation.

**CAUTION ATTENTION**

LASER LIGHT - DO NOT STARE INTO BEAM
 630-680 nm 1.0mW | 630-680 nm 1.0 mW
 CLASS II LASER PRODUCT | PRODUIT LASER CLASSE II

CAUTION - Laser light when open. Do not stare into beam.
 ATTENTION - Lumière laser lors de l'ouverture ne pas regarder fixement dans le faisceau.

Complies with U.S.A. 21CFR subchapter J Part 1040

North America

Corporate Headquarters
 6001 36th Avenue West
 Everett, Washington 98203
 tel: 425.348.2600
 fax: 425.355.9551

550 2nd Street S.E.
 Cedar Rapids, Iowa 52401
 tel: 319.369.3100
 fax: 319.369.3453

Media Supplies
 9290 Le Saint Drive
 Fairfield, Ohio 45014
 tel: 513.874.5882
 fax: 513.874.8487

Canada

7065 Tranmere Drive
 Mississauga, Ontario
 L5S 1M2 Canada
 tel: 905.673.9333
 fax: 905.673.3974

**Europe/
Middle East & Africa
Headquarters**

Sovereign House
 Vastern Road
 Reading RG1 8BT
 United Kingdom
 tel: 44.118.987.9400
 fax: 44.118.987.9401

Asia

Asia Regional Office
 26-16 International Plaza
 10 Anson Road
 Singapore 079903
 tel: 65.6324.8391
 fax: 65.6324.8393

Beijing Representative Office

29 FL, Unit A1, China Merchant Tower
 118 Jian Guo Road
 Chaoyang District, Beijing 100022
 Tel: 86 10.5165.5922
 Fax: 86 10.6567.6778

Australia

Level 7, 200 Pacific Highway
 Crowns Nest, NSW 2065
 Australia
 tel: 61.2.9492.4400
 fax: 61.2.9954.6300

South America & Mexico

Intermec South America Ltda.
 Rua Samuel Morse 120 9 andar
 Brooklin CEP04576-060
 São Paulo, SP
 Brazil
 tel: 55.11.5502.6770

Intermec Technologies de Mexico

Av Tamaulipas #141, Primer Piso
 Col. Hipodromo Condesa
 Mexico, DF, 06140 Mexico
 tel: 525.55.241.4800
 fax: 525.55.211.8121

Internet

www.intermec.com

Sales

800.347.2636
 (toll free in N.A.)
 tel: 425.348.2726

Service and Support

800.755.5505
 (toll free in N.A.)
 tel: 425.356.1799

Copyright © 2005 Intermec Technologies Corporation. All rights reserved. Intermec is a registered trademark of Intermec Technologies Corporation. All other trademarks are the property of their respective owners. Printed in the U.S.A. 611618-01C 07/05

In a continuing effort to improve our products, Intermec Technologies Corporation reserves the right to change specifications and features without prior notice.

Intermec
 expect MORE®